



DONNÉES TECHNIQUES / TECHNICAL SPECS

Dimension std / Std Size: 8' x 4' (2.44 m x 1.22 m) / 32 sq/ft (2.973 sq/m)

Poids au pied carré / Weight per Square Foot: 2.69 lbs. / 43 oz. / 1.22 kg. / 1219 grams

Poids au metre carré / Weight per Square Meter: 28.60 lbs. / 12.97 kg.

Épaisseur en fonction du profil de traction / Total thickness with threads :

MM Machine Rugged / Machine Rugged ½" mat + 3/8" cleat + 3/8" cleat = 1 ¼" total

PM Pedestrian / Machine Rugged ½" mat + 3/8" cleat = 7/8" total

Profil de traction Machine / Machine Rugged Traction Surface:

Double-traction tread design includes two parallel traction treads positioned at a 90-degree angle to adjacent double traction tread sets.

Profil de traction piétons / Pedestrian Traction Surface:

Pedestrian friendly alternating cross shaped traction design. Can be placed under with PM threads mats in order to be softer on sub surfaces and keep max traction for vehicles.

Poids et dimensions / Weight and Size : 8' x 4' (2.44m x 1.22m) 86lbs (39.01kg)

8' x 2' (2.44m x 0.609m) 43lbs (19.5 kg)

Couleurs / Colors: Black (UV), White.

Matériau / Material: High-Density Polyethylene (HDPE) post-industrial recycled plastic

Capacité de charge / Weight Loading: Variable, depending on sub-surface, up to 80 tons capacity.

Résistance à la compression - Compressive Strength: 2,843 psi (ASTM D695-02a)

Résistance aux flames / Flammability Resistance: UL-94 HB Rating

Préparation des surfaces / Ground Surface:

Terraplak is designed to be used with no ground preparation over grass, gravel, soil, concrete, asphalt, mud and sandy soil conditions.

Connexions / Connection System:

Terraplak has eight holes: one in each corner and four in the center line (two on each 8ft side) to create multi-directional roadways of nearly any size or shape. Mats can be connected using metal connectors (mosts do not require tools to install)

Livraison / Shipping: Pallet maximum is 30 units (4' x 8')

20' Ocean Container: 250 – 4' x 8' unit order and/or equal to 29,240lbs.

40' Ocean Container: 500 – 4' x 8' unit order and/or equal to 43,000lbs.

Garantie / Warranty:

7 ans contre les defaults entraînant le craquement ou la déchirure en usage normal

7 years against cracking and breaking under normal use.